


Rockwell International ST0130RB0078 Silicone Rubber Tape
 Operating temperature: -65°F to +500°F / -54°C to 260°C; Brittle temperature -85°F / -65°C
FlameShield™ Silicone Rubber Self Fusing Compression & Stretch Electrical Insulating Tape
Self Binding Self-Fusing Tape - High Temperature, Heat & Flame Resistant



- Self-bonds / self fuses / self amalgamating. No sticky residue or adhesive when removed. Starts fusing within minutes, fully bonded within hours. Excellent cold weather performance. Makes an excellent compression tape.
- Excellent for sealing ends of firesleeve: prevents sleeve from absorbing contamination and wicking liquids. Excellent for wrapping electrical & mechanical connections and splices. Makes clean and neat installations of cables, wires and hoses. Makes an instant separation bumper and provides vibration dampening.
- Meets Mil-I-46852 and AA59163 and other proprietary specifications.
- CofC available.

FlameShield™ Rockwell International ST0130RB0078 High Temperature Silicone Rubber Self Fusing Compression/Stretch Tape		
Part Number	Tape Width Inches / mm	Tape Thickness Inches / mm
ST0130RB0078 Type I Tape		
T-SR-ST0130RB0078-1T	As per specification	As per specification
ST0130RB0078 Type II Tape		
T-SR-ST0130RB0078-2R-12	As per specification	0.012 / 0.30
T-SR-ST0130RB0078-2R-15	As per specification	0.015 / 0.38
T-SR-ST0130RB0078-2R-20	As per specification	0.020 / 0.51

- Standard roll length is 36 feet / 12 Yards / 10.9 Metres; other lengths available.
- All versions of ST0130RB0078 are Oxide-Red

These tapes are guaranteed to meet specification for 1 year from date of manufacture providing tapes are stored dry at 21°C +/- 3°C or 70°F +/- 5°F. Standard tapes have an interleaved liner of polyethylene. Polyester liner available.